

USER'S MANUAL

Product installation , Maintenance

Maintenance



Function :
Check whether there is a leak in the connection and the function is normal. Before above installation, flush any contaminants in supply lines for 30-60 seconds until water is clean. To avoid any contaminants stuck in the faucet and affect the faucet function usage.



Maintenance:
Check and clean all parts and replace if necessary. Stop the water supply and perform maintenance work.



Cleaning:
Clean with fresh water and soft cloth. Do not use below cleansers to damage the faucet surface,



abrasive sponges
cleanser
organic solvent or acid cleansers
scale removers
household vinegar or vinegar-based cleansers
other sensitive chemical cleansers

Patented Note: all faucet models in this manual are patented. Do not allow for any copy in this manual

Installation List

S/N	Description	No.
1	Faucet	1
2	Instruction	1
3	Fasten parts	1
4	2.5mm Allen key	1
5	Hot & cold inlet hose	1
6	Spanner	1
7	Gloves	1
8	Screwdriver	1

BASIN / KITCHEN MIXER

1. Make a hole on the corner at 45° - 45mm.
2. Push any contaminants in supply lines for 30-60 seconds until water is clean.
3. Pass all the fasten parts (3) in correct direction through the hole from the side (2). Then make sure that they go through the hole from down to top counter.

4. Fit the hot/cold inlet hose (5) to the faucet.

5. Fit the fasten parts (3), and then tighten the Allen Key to the faucet.

6. Fasten the screws nut from (2) with screwdriver (7).

7. Fasten the other end of the hose (5) to the inlet connector by spanner (8).

8. Fit the hot/cold inlet hose (5) to the faucet.

Installation List

S/N	Description	No.
1	Faucet	1
2	Instruction	1
3	Fasten parts	1
4	2.5mm Allen Key	1
5	Pull out hose	1
6	Hot & cold inlet hose	1
7	Weight ball	1
8	Spanner	1
9	Screwdriver	1
10	Gloves	1

PULL DOWN KITCHEN MIXER

1. Make a hole on the counter at 45° - 45mm.
2. Push any contaminants in supply lines for 30-60 seconds until water is clean.
3. Pass all the fasten parts (3) in correct direction through the hole from the side (2). Then make sure that they go through the hole from down to top counter. Fit the hole accordingly.

4. Fit the hot/cold inlet hose (5) to the faucet.

5. Tighten the screws nut from (2) with screwdriver (9) as above picture.

6. Screw up the pull out hose (5) to the other side, and screw the weight ball (7) and adjust to the pull out hose.

7. Fasten the other end of the hose (5) to the inlet connector by spanner (8).

Installation List

S/N	Description	No.
1	Opener	1
2	Hex Allen key	1
3	Fasten parts	1
4	Protective sleeve	1
5	Screw set	1

CONCEALED BASIN MIXER (A)

1. Before installation, please fit a protective sleeve with depth 45-55mm, and mark the hole and position (1) for the concealed body (1), then fasten the screws. Turn on the water to check if any leakage.

2. Take off the pipe connector from tap (1) and turn it left. Then, insert to the body (5) and fasten by Allen Allen key (2).

3. Take off the protective sleeve (7), and fit the fast plate (4) to concealed body (5) in right position. Then, fit the screws (5) to the fast (5) by screws set (1).

4. Fit the tap (1) to the faucet concealed body (5) and screw it right.

Installation List

S/N	Description	No.
1	Opener	1
2	Hex Allen key	1
3	Fasten parts	1
4	Protective sleeve	1
5	Screw set	1

CONCEALED BASIN MIXER (B)

1. Before installation, please fit a protective sleeve with depth 45-55mm, and mark the hole and position (1) for the concealed body (1), then fasten the screws. Turn on the water to check if any leakage.

2. Fit the tap (1) to the faucet concealed body (5) and screw it right. Then, fit the screws (5) to the fast (5) by Allen Allen key (2).

3. Turn off the water to check if any leakage. Then, take the protection sleeve, and fit the fast plate (4) to the tap (1) by Allen Allen key (2). Turn on the water to check if any leakage.

4. Fit the tap (1) to the faucet body (5). Then, fit the handle (1) to Mixer body (5).

Installation List

S/N	Description	No.
1	Opener	1
2	Hex Allen key	1
3	Fasten parts	1
4	Protective sleeve	1
5	Screw set	1

SHATTAF MIXER

1. Before installation, please fit a protective sleeve with depth 45-55mm, and mark the hole and position (1) for the concealed body (1), then fasten the screws. Turn on the water to check if any leakage.

2. Fit the tap (1) to the faucet concealed body (5) and screw it right. Then, fit the screws (5) to the fast (5) by Allen Allen key (2).

3. Turn off the water to check if any leakage. Then, take the protection sleeve, and fit the fast plate (4) to the tap (1) by Allen Allen key (2). Turn on the water to check if any leakage.

4. Connect the handle to one end to the handle (3), and other end to the shattaf (1).

Installation List

S/N	Description	No.
1	Opener	1
2	Hex Allen key	1
3	Fasten parts	1
4	Protective sleeve	1
5	Screw set	1

BATH & SHOWER MIXER

1. Tap around the wall "2" pipes (2), and make sure to be wall water tight. Then fasten tight by spanner. After, flush any contaminants in supply lines for 30-60 seconds until water is clean.

2. Screw up the wall flange (2) to the wall (2).

3. Fit the hot/cold inlet hose (5) to the faucet (1) by spanner.

4. Fit the shower holder (3) to the wall by screw set (5), and fasten to measurement.

5. Connect the shower hose (4) one end to the faucet (1), the other end to shower (4).

SHOWER COLUMN

SN	Description	No.1
1	Water outlet	1
2	Shower head	1
3	Shower hose	1
4	Shower arm	1
5	Shower column	1
6	Shower column accessories	1
7	Shower column	1
8	Shower column	1
9	Shower column	1
10	Shower column	1
11	Shower column	1
12	Shower column	1

1. Tape around the wall "2" pipes (1), and screw them to the wall with screws. Then, tighten right by spanner. After, flush any contaminants in supply lines for 30-60 seconds until water is clean.
2. Screw up the wall flange (1) to the "2" pipes (1).
3. Put the shower column accessories (1) to the shower column (7) and mark the position of the shower column holder (8) to the wall. Then, fix the shower column holder (8) to the wall with the screw.
4. Fix the shower column accessories (1) to the shower column (7) and connect the shower column (7) to the shower holder (8) by the wall flange.
5. Fix the shower column accessories (1) to the shower column (7) and connect the shower column (7) to the shower holder (8) by the wall flange.
6. Fix the shower column accessories (1) to the shower column (7) and connect the shower column (7) to the shower holder (8) by the wall flange.

WIDESPREAD BATHTUB FAUCET

SN	Description	No.1
1	Water outlet	1
2	Water outlet	1
3	Water outlet	1
4	Water outlet	1
5	Water outlet	1
6	Water outlet	1
7	Water outlet	1
8	Water outlet	1
9	Water outlet	1
10	Water outlet	1
11	Water outlet	1
12	Water outlet	1

1. Make each parts (1, 2, 3 & 4) installed to the shower hole (according to correct dimension in above picture). Each handle each screw hole by spanner and Allen key.
2. Fix each part (5, 6 & 7) accordingly to each part in shower. Then, fix the vertical part (8) to shower hole (9).
3. Flush any contaminants in supply lines for 30-60 seconds until water is clean. Fix the other end of hot hose (5) to single valve by spanner.

CONCEALED SHOWER SET (TWO FUNCTION)

SN	Description	No.1
1	Shower set	1
2	Shower set	1
3	Shower set	1
4	Shower set	1
5	Shower set	1
6	Shower set	1
7	Shower set	1
8	Shower set	1
9	Shower set	1
10	Shower set	1
11	Shower set	1
12	Shower set	1

1. Before installation, plug a primer and pressure with 40-60psi, and flush the supply and install all. Fix the concealed body (1) to the wall with the screws. Turn on the valves to check if any leakage.
2. Take off the protection sleeve from the faucet (1), fix the body (7) to the wall.
3. Fix the shower set (1) to the wall, and screw the shower set (2) to the shower set (1). Then, fix the shower holder with connector (3) to the wall.
4. Fix the shower hose (4) and hand shower (5) to the shower holder (3).

FLOOR STAND BATH MIXER (A)

SN	Description	No.1
1	Floor stand	1
2	Floor stand	1
3	Floor stand	1
4	Floor stand	1
5	Floor stand	1
6	Floor stand	1
7	Floor stand	1
8	Floor stand	1
9	Floor stand	1
10	Floor stand	1
11	Floor stand	1
12	Floor stand	1

1. Put the mixer handle (1) through the hole (2) and fix to the wall with the lock (3). Then, fix the floor stand (4) to the wall with the screw (5).
2. Mark the right position to the floor by assembled handle in step 1.
3. Drill out the hole as per the marked position. Then fix the expansion screws (7) and insert to the fixing seat (8).
4. Drill out the hole as per the marked position. Then fix the expansion screws (7) and insert to the fixing seat (8).
5. Flush any contaminants in supply lines for 30-60 seconds until water is clean. Then, fix the assembled faucet to the wall (9).
6. Complete the picture.

WIDESPREAD BASIN FAUCET

SN	Description	No.1
1	Water outlet	1
2	Water outlet	1
3	Water outlet	1
4	Water outlet	1
5	Water outlet	1
6	Water outlet	1
7	Water outlet	1
8	Water outlet	1
9	Water outlet	1
10	Water outlet	1
11	Water outlet	1
12	Water outlet	1

1. Make each parts (1, 2, 3 & 4) installed to the shower hole (according to correct dimension in above picture). Each handle each screw hole by spanner and Allen key.
2. Fix each hoses (5, 6 & 7) accordingly to each part in above picture.
3. Flush any contaminants in supply lines for 30-60 seconds until water is clean. Fix the other end of hot hose (5) to single valve by spanner.

WALL MIXER

SN	Description	No.1
1	Water outlet	1
2	Water outlet	1
3	Water outlet	1
4	Water outlet	1
5	Water outlet	1
6	Water outlet	1
7	Water outlet	1
8	Water outlet	1
9	Water outlet	1
10	Water outlet	1
11	Water outlet	1
12	Water outlet	1

1. Before installation, plug a primer and pressure with 40-60psi, and flush the supply and install all. Fix the concealed body (1) to the wall with the screws.
2. Fix the protection sleeve from the faucet (1), fix the body (7) to the wall (8). Then, install the handle (9) and handle (10) to the body (1).
3. Fix the handle (11) by screw and (12).

CONCEALED SHOWER SET (THREE FUNCTION)

SN	Description	No.1
1	Shower set	1
2	Shower set	1
3	Shower set	1
4	Shower set	1
5	Shower set	1
6	Shower set	1
7	Shower set	1
8	Shower set	1
9	Shower set	1
10	Shower set	1
11	Shower set	1
12	Shower set	1

1. Before installation, plug a primer and pressure with 40-60psi, and flush the supply and install all. Fix the concealed body (1) to the wall with the screws. Turn on the valves to check if any leakage.
2. Take off the protection sleeve from the faucet (1), fix the body (7) to the wall (8). Then, install the handle (9) and handle (10) to the body (1).
3. Fix the shower set (1) to the wall, and screw the shower set (2) to the shower set (1). Then, fix the shower holder with connector (3) to the wall.
4. Fix the shower hose (4) and hand shower (5) to the shower holder (3). Fix the shower hose (6) to the shower set (1).

FLOOR STAND BATH MIXER (B)

SN	Description	No.1
1	Floor stand	1
2	Floor stand	1
3	Floor stand	1
4	Floor stand	1
5	Floor stand	1
6	Floor stand	1
7	Floor stand	1
8	Floor stand	1
9	Floor stand	1
10	Floor stand	1
11	Floor stand	1
12	Floor stand	1

1. Installation and operation steps of concealed bath (see below).
2. Remove the protection cover step by step.
3. Fix the flange to the bottom of faucet correctly.
4. Fix the flange to the bottom of faucet correctly.
5. Fix the flange to the bottom of faucet correctly.
6. Fix the flange to the bottom of faucet correctly.